

Fixed angle notching machine SAF 204 / SAF 206

Product details:

- **Code:** SAF 204 / SAF 206
- **Category:** Fixed angle notcher 4/6 mm
- **Brand:** AVM Srl Sheet Metal Machinery
- **Download:** [Product specifications sheet](#)



Machine Dimensions

| | | |
|----------------------------------|----|------------------|
| Overall dimensions (L x P x H) | mm | 915 x 625 x 1000 |
| Approximate weight | kg | 395/410 |

Technical Specifications

| | | |
|-----------------------------------|----|-----------------|
| Blade length | mm | 205 |
| Max. thickness on sheet metal | mm | 6/4 |
| Max. thickness on stainless steel | mm | 4/3 |
| Sheet clamps | - | ONLY FOR SAF206 |
| Automatic clearance adjustment | - | optional |
| Motor power | kW | 3 |
| Strokes/minute | Nm | 50 |
| Bench dimentions | mm | 915 x 625 |
| Height of work bench | mm | 930 |

| | | |
|-----------------------------|---|----------|
| Tank capacity | L | 25 |
| Cutting angle | ° | 90 |
| Electronic stroke regulator | - | optional |

Description

Notching station:

Our **hydraulic notching machines** are equipped with **two cylinders** to ensure **smooth and accurate notching**.

The work bench is **sturdy and wide**. It is fitted with **scaled aluminium rods with a triple function** for measuring different types of notch. Thanks to rectified backgauges and scaled rods, operators can rapidly and accurately **position** workpieces.

The many **T-slots on the bench** allow for the use of **mechanical and/or hide-away backstops** to perform **complex notching cycles**.

The exceptional stability of the notching unit is guaranteed by side columns.

The internal backstop will allow you to **transform the notching machine into a small shearing unit** to cut strips with a length of up 200 mm.

The configuration of the blade head allows you to obtain **cuts that are longer than the blade**.

A **hand guard** allows you to work in the safest manner possible and with no impaired visibility.

AVM notching machines can be fitted with a handy **electronic stroke regulator** with digital readout (optional).

The control board allows you to select **single-stroke or jog operation**, to allow for customised work and to optimise your work cycle, thanks also to the **electronic stroke regulator** that locks the stroke in an established position (optional).

All of our notching machines are fitted with a **box for scrap collection**.

Optional accessories:

- [Electronic stroke regulator](#)
- [Sheet clamping cylinders](#)
- Special voltage ratings
- [Mechanical and/or Disappearing Stops](#)

Spare parts:

- [Upper blades Kit *](#)
- [Fixed lower blades Kit *](#)
- [Self-adjusting lower blades Kit *](#)
- [Scaled rods](#)
- [Square body assembly](#)
- [Square rods](#)

N.B.: *All blades can also be provided in HSS version